

# PRODUCT DATASHEET LED ECO Hi-Watt 120 20 W/3000 K E27

LED ECO HIGH WATT | T shape bulb



#### Areas of application

- Especially suitable for the food sector
- Warehouses
- Supermarkets and department stores
- Suitable for indoor applications.

#### **Product benefits**

- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Wide beam angle: 200°
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam

#### Product features

- Lifetime: up to 12,000 h
- Good color rendering index  $R_a$ : ≥ 80
- Overtemperature protection
- Surge protection: up to 2,000 V
- $-\,$  Luminous efficacy: up to 100 lm/W
- Mercury-free lamps
- Minimum start voltage at 180 VAC



## TECHNICAL DATA

## Electrical data

Nominal wattage	20 W
Construction wattage	20.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	120 W
Nominal current	160 mA
Type of current	AC
Operating frequency	50 Hz
Mains frequency	50 Hz
Power factor $\lambda$	0.50

## Photometrical data

Luminous flux	1800 lm
Nominal useful luminous flux 90°	1800 lm
Luminous efficacy	90 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	≥80
Light color	830
Standard deviation of color matching	≤6 sdcm

# Light technical data

Beam angle	180 °
Starting time	< 0.5 \$

# Dimensions & Weight

Overall length	135.00 mm
Diameter	80.00 mm
Maximum diameter	80 mm

October 16, 2025, 08:23:11 LED ECO Hi-Watt 120 20 W/3000 K E27

Product weight	65.00 g
Temperatures & operating conditions	
Ambient temperature range	-20+40 °C
Lifespan	
Number of switching cycles	100000
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
Certificates & Standards	
Standards	CB / RoHS
Country-specific categorizations	
Order reference	LE HW 20W/830 2
LOGISTICAL DATA	
Temperature range at storage	-20+80 °C
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface)	E27
Length	135.00 mm
Height	80.00 mm
Width	80.00 mm

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075683051	Folding box 1	81 mm x 81 mm x 148 mm	100.00 g	0.97 dm <sup>3</sup>
4058075683068	Shipping box 10	421 mm x 178 mm x 175 mm	1329.00 g	13.11 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

October 16, 2025, 08:23:11 LED ECO Hi-Watt 120 20 W/3000 K E27 When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.