

# PRODUCT DATASHEET Undercabinet Spot Magnet 75mm 8.5W 830

Spot Magnet | Undercabinet spot luminaire in round shape with magnet closure



### Areas of application

- Kitchens
- Living areas
- Undercabinet lighting

### Product benefits

- Modern design with very flat luminaire base
- Spotlights for Undercabinet illumination
- Magnetic closure
- Easy mounting

# TECHNICAL DATA

# Electrical data


| Nominal wattage                                             | 8.50 W                |
|-------------------------------------------------------------|-----------------------|
| Nominal voltage                                             | 220240 V              |
| Mains frequency                                             | 5060 Hz               |
| Nominal current                                             | 49.000 mA             |
| Max. number of luminaires per miniature circuit breaker B16 | 64                    |
| Max. number of luminaires per miniature circuit breaker C16 | 64                    |
| Power factor $\lambda$                                      | > 0.5                 |
| Total harmonic distortion                                   | < 60 %                |
| Protection class                                            | III                   |
| Operating mode                                              | Integrated LED driver |

### Photometrical data

| Luminous flux                                | 390 lm     |
|----------------------------------------------|------------|
| Luminous efficacy                            | 45 lm/W    |
| Color temperature                            | 3000 K     |
| Light color (designation)                    | Warm White |
| Color rendering index Ra                     | > 80       |
| Standard deviation of color matching         | 6 sdcm     |
| Photobiological safety group acc. to EN62778 | RG1        |
| Beam angle                                   | 120°       |

# Dimensions & Weight

| Diameter       | 75.00 mm |
|----------------|----------|
| Height         | 7.00 mm  |
| Product weight | 240.00 g |



0112E11071E111E110101111111111111

## Materials & Colors

| Product color                              | White            |
|--------------------------------------------|------------------|
| Housing color                              | White            |
| Body material                              | Aluminum Plastic |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C           |
| Mercury content                            | 0.0 mg           |

### **Application & Mounting**

| Ambient temperature range | -20+40 °C     |
|---------------------------|---------------|
| Type of connection        | Cable, 3-pole |
| Type of protection        | IP20          |
| Dimmable                  | Yes           |
| Type of dimming           | CLICKSWITC    |
| Mounting type             | Surface       |
| Application environment   | Indoor        |
| With light source         | Yes           |
| Replaceable light source  | No            |

# Lifespan

| Lifespan L7 | /B50 at 25 °C | 30000 h <sup>1)</sup> |
|-------------|---------------|-----------------------|
|             |               |                       |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

| Standards                                            | CE / UKCA       |
|------------------------------------------------------|-----------------|
| Luminaire with limited surface temperature, "D sign" | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

### **EQUIPMENT / ACCESSORIES**

- Mounting screws and dowels included

# Safety advice

- The luminaires are not suitable for covering with thermally insulated material.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

# DOWNLOAD DATA

|     | Documents and certificates             | Document name            |
|-----|----------------------------------------|--------------------------|
| POF | User instruction / safety instructions | UNDERCABINET SPOT MAGNET |

|                       | Documents and certificates                                            | Document name           |
|-----------------------|-----------------------------------------------------------------------|-------------------------|
| PDF Legal information |                                                                       | Safety insert G11222443 |
| PDF                   | PDF Declarations of conformity CE Declaration UNDERCABINET SPOTMAGNET |                         |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854462450 | Folding box                  | 55 mm x 84 mm x 270 mm               | 323.00 g     | 1.25 dm <sup>3</sup>  |
| 4099854462467 | Shipping box<br>8            | 290 mm x 235 mm x 195 mm             | 2948.00 g    | 13.29 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.