

# PRODUCT DATASHEET Ceiling Essential 250mm 13W 4000K

Essentials Ceiling | Essential Ceiling luminaires for basic user purposes



#### Areas of application

- Living areas

#### Product benefits

- Simple installation thanks to light-weight design
- Decorative wall light

#### **Product features**

- Wall and ceiling luminaire



## TECHNICAL DATA

## Electrical data


Nominal wattage	13.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	65.000 mA	
Inrush current time T <sub>h50</sub>	6.6 µs	
Max. number of luminaires per miniature circuit breaker B16	98	
Max. number of luminaires per miniature circuit breaker C16	123	
Power factor $\lambda$	> 0.70	
Total harmonic distortion	< 70 %	
Protection class	I	
Operating mode	Integrated LED driver	

## Photometrical data

Luminous flux	960 lm	
Total luminous flux of contained light sources	1500 lm	
Luminous efficacy	73 lm/W	
Color temperature	4000 K	
Light color (designation)	Cool White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	120 °	

## Dimensions & Weight

Diameter	250.00 mm
Height	91.00 mm
Product weight	330.00 g



## Materials & Colors

Product color	White	
Housing color	White	
Body material	Plastic	
Cover material	Polymethylmethacrylate (PMMA)	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

## **Application & Mounting**

Ambient temperature range	-20+40 °C	
Type of connection	Cable, 3-pole	
Type of protection	IP20	
Protection class IK (shock resistance)	IK03	
Dimmable	No	
Mounting type	Surface	
Application environment	Indoor	
With light source	Yes	
Replaceable light source	No	

## Lifespan

Lifespan L70/B50 at 25 °C	20000 h <sup>1)</sup>
Number of switching cycles	50000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# Certificates & Standards

Standards	CE / UKCA	
Luminaire with limited surface temperature, "D sign"	No	
Ball shot safe	No	
Replaceable light source (EPREL)	Not replaceable	

#### Additional product data

Number of illuminants	empty
-----------------------	-------

#### **EQUIPMENT / ACCESSORIES**

- Mounting screws and dowels included

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	User instruction / safety instructions	CEILING ESSENTIAL
PDF	Legal information	Safety insert G11219578
PDF	Declarations of conformity	CEILING ESSENTIAL
PDF	Declarations of conformity UKCA	Fixed LUM

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854445187	Folding box	189 mm x 189 mm x 644 mm	593.00 g	23.00 dm <sup>3</sup>
4099854445194	Shipping box 10	575 mm x 510 mm x 305 mm	5930.00 g	89.44 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.