

PRODUCT DATASHEET Floodlight Essential 100W 4000K

Essentials Floodlights | Essential Floodlights for basic user purposes



Areas of application

- Outdoor
- Building facades

Product benefits

- IP65 protection is suitable for outdoor application
- White satin-frosted diffuser for uniform glare-free light

Product features

- IP65 outdoor floodlight
- Adjustable light angle



TECHNICAL DATA

Electrical data

| Nominal wattage | 100.00 W |
|---|-----------------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 450.000 mA |
| Inrush current time T _{h50} | 120 μs |
| Max. number of luminaires per miniature circuit breaker B16 | 23 |
| Max. number of luminaires per miniature circuit breaker C16 | 23 |
| Power factor λ | > 0.90 |
| Total harmonic distortion | < 20 % |
| Protection class | I I |
| Operating mode | Integrated LED driver |

Photometrical data

| Luminous flux | 10000 lm |
|--|------------|
| Total luminous flux of contained light sources | 11500 lm |
| Luminous efficacy | 100 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | 6 sdcm |
| Photobiological safety group acc. to EN62778 | RG0 |
| Beam angle | 110° |

Dimensions & Weight

| Length | 270.00 mm |
|----------------|-----------|
| Width | 30.00 mm |
| Height | 222.00 mm |
| Product weight | 1000.00 g |
| Cable length | 250 mm |



FL ESSENTIAL 100W 840 BK

Materials & Colors

| Product color | Black |
|--|----------|
| Housing color | Black |
| Body material | Aluminum |
| Cover material | Glass |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|--|---------------|
| Temperature range at storage | -25+80 °C |
| Type of connection | Cable, 3-pole |
| Type of protection | IP65 |
| Protection class IK (shock resistance) | IK06 |
| Dimmable | No |
| Mounting type | Surface |
| With light source | Yes |
| Replaceable light source | No |

Lifespan

| Lifespan L70/B50 at 25 °C | 25000 h ¹⁾ |
|----------------------------|-----------------------|
| Number of switching cycles | 12500 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| Standards | CE / UKCA |
|--|-----------------|
| Luminaire with limited surface temperature, "D sign" | No |
| Replaceable light source (EPREL) | Not replaceable |

Additional product data

| Number of illuminants empty |
|-----------------------------|
|-----------------------------|

EQUIPMENT / ACCESSORIES

- Connection cable included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| Documents and certificates Do | | Document name | |
|---|---------------------------------|---------------------------------|--|
| User instruction / safety instructions FL ESSENTIAL_S | | FL ESSENTIAL_SENSOR | |
| PDF | Legal information | rmation Safety insert G11220428 | |
| PDF | Declarations of conformity | FL ESSENTIAL | |
| PDF | Declarations of conformity UKCA | FLOODLIGHT ESSENTIAL | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854429576 | Folding box 1 | 42 mm x 282 mm x 238 mm | 1225.00 g | 2.82 dm ³ |
| 4099854429583 | Shipping box 4 | 302 mm x 187 mm x 265 mm | 4900.00 g | 14.97 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.