

# PRODUCT DATASHEET Orbis Slim Moia 380mm 24W 830 BK

Ceiling Moia | LED ceiling luminaires with metal ring



### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

### Product benefits

- Very homogenous light
- Elegant design

### **Product features**

- Decorative domestic lighting
- Ceiling luminaire with advanced LED technology



# TECHNICAL DATA

# Electrical data

Nominal wattage	24.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	122.000 mA
Inrush current time T <sub>h50</sub>	100 μs
Power factor $\lambda$	≥0.7
Total harmonic distortion	< 70 %
Protection class	1
Operating mode	Mains voltage

## Photometrical data

Luminous flux	1800 lm
Total luminous flux of contained light sources	2700 lm
Luminous efficacy	75 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120°

# Dimensions & Weight

Diameter	380.00 mm
Height	40.00 mm
Product weight	1164.00 g



## Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

## **Application & Mounting**

Ambient temperature range	-2040 °C
Temperature range at storage	-20+60 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	Yes
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	50000 h <sup>1)</sup>
Number of switching cycles	25000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

# Additional product data

Number of illuminants	empty

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in

the event of a fault must be continuously connected to the protective earthing conductor.

- Check wall-ceiling for suitability. If uncertain, seek professional advice.

### **DOWNLOAD DATA**

Documents and certificates		Document name	
User instruction / safety instructions  ORBIS SLIM MOIA  Legal information  Safety insert G11219601		ORBIS SLIM MOIA	
		Safety insert G11219601	
PDF	PDF Declarations of conformity CE Declaration Orbis Moia 380		
PDF	Declarations of conformity UKCA	UKCA Declaration Orbis Moia 380	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854450105	Folding box 1	48 mm x 387 mm x 387 mm	1510.00 g	7.19 dm³
4099854450112	Shipping box 4	407 mm x 215 mm x 415 mm	6040.00 g	36.31 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.