

# PRODUCT DATASHEET Orbis Dublin 390 mm 24W 830 SI

ORBIS DUBLIN | LED ceiling luminaires with plastic ring



#### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

#### Product benefits

- Very homogenous light
- Elegant design

#### **Product features**

- Decorative domestic lighting
- Ceiling luminaire with advanced LED technology



# TECHNICAL DATA

# Electrical data

Nominal wattage	24.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	185.000 mA
Max. number of luminaires per miniature circuit breaker B16	35
Max. number of luminaires per miniature circuit breaker C16	48
Power factor λ	> 0.5
Total harmonic distortion	< 101 %
Protection class	1
Operating mode	Electronic control gear (ECG)

# Photometrical data

Luminous flux	1600 lm
Luminous efficacy	66 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °

# Dimensions & Weight

	Diameter	390.00 mm
Ī	Height	75.00 mm
Ī	Product weight	740.00 g



# Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Metal
Cover material	Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	Yes
Replaceable light source	No

#### Lifespan

Lifespan L70/B50 at 25 °C	50000 h <sup>1)</sup>
Number of switching cycles	25000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

# Additional product data

Nur	mber of illuminants	empty

# Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in

the event of a fault must be continuously connected to the protective earthing conductor.

- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### **DOWNLOAD DATA**

Documents and certificates Document name		Document name
PDF	User instruction / safety instructions	ORBIS
PDF	Legal information	Safety insert G11219601
PDF	Declarations of conformity	ORBIS LONDON DUBLIN BERLIN
PDF	Declarations of conformity UKCA	ORBIS LONDON DUBLIN BERLIN

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854447747	Folding box 1	410 mm x 75 mm x 410 mm	1220.00 g	12.61 dm <sup>3</sup>
4099854447754	Shipping box 5	430 mm x 420 mm x 430 mm	6463.00 g	77.66 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.