

# PRODUCT DATASHEET

## WP BATTEN 600 14-24W TRI EM MS

TRI COLOUR MULTI WATTAGE WEATHERPROOF BATTEN | Damp-proof luminaires



### Areas of application

- Car parks
- Storage rooms
- Outdoor applications
- Passages, underpasses
- Workshops, assembly lines

### Product features

- Available in 3 length options: 600 mm, 1200 mm, 1500 mm
- TRI CCT (3000K/4000K/6500K)
- Beam angle: 120°
- High luminous efficacy: up to 120 lm/W
- Type of protection: IP65
- Impact resistance: IK08
- Polycarbonate housing
- Lifetime up to 50,000 h

TECHNICAL DATA

Electrical data

|                 |             |
|-----------------|-------------|
| Nominal wattage | 24.00 W     |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz  |

Photometrical data

|                           |                                         |
|---------------------------|-----------------------------------------|
| Luminous efficacy         | 110 lm/W                                |
| Light color (designation) | Warm White / Cool White / Cool Daylight |
| Color rendering index Ra  | 80                                      |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 655.00 mm |
| Width          | 115.00 mm |
| Height         | 86.00 mm  |
| Product weight | 1417.00 g |

Materials & Colors

|                 |                    |
|-----------------|--------------------|
| Product color   | Gray               |
| Housing color   | Gray               |
| Body material   | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

Application & Mounting

|                          |         |
|--------------------------|---------|
| Type of protection       | IP65    |
| Dimmable                 | No      |
| Mounting type            | Surface |
| Replaceable light source | No      |

BATTERY

|                    |        |
|--------------------|--------|
| Battery size [GMS] | Others |
|--------------------|--------|

Certificates & Standards

|                                  |                 |
|----------------------------------|-----------------|
| Replaceable light source (EPREL) | Not replaceable |
|----------------------------------|-----------------|

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume   |
|---------------|------------------------------|--------------------------------------|--------------|----------|
| 4099854212635 | Folding box<br>1             | 660 mm x 120 mm x 90 mm              | 1477.00 g    | 7.13 dm³ |

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4099854212642 | Shipping box<br>6            | 675 mm x 250 mm x 282 mm             | 9662.00 g    | 47.59 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.