

# PRODUCT DATASHEET Decor Spot Moon 1Spot W 5.5W 830 Black

DECOR SPOT MOON | Ceiling mounted luminaires with adjustable spotlights



#### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

#### Product benefits

- High-quality look and feel
- Functional and minimalistic design
- Easy mounting

#### **Product features**

- Luminaire family features five versions with up to 4 spot heads
- Adjustable heads
- Housing material: metal



# TECHNICAL DATA

# Electrical data

Nominal wattage	5.50 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	40.000 mA
Inrush current time T <sub>h50</sub>	320 µs
Max. number of luminaires per miniature circuit breaker B16	320
Max. number of luminaires per miniature circuit breaker C10	200
Max. number of luminaires per miniature circuit breaker C16	320
Power factor λ	> 0.5
Total harmonic distortion	65 %
Protection class	1
Operating mode	Mains voltage

# Photometrical data

Luminous flux	280 lm
Total luminous flux of contained light sources	500 lm
Luminous efficacy	50 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	6 sdcm
Photobiological safety group acc. to EN62778	RG1
Beam angle	115 °

# Dimensions & Weight

Length	120.00 mm
Width	120.00 mm
Height	94.00 mm
Product weight	300.00 g

Black



# DECOR SPOT MOON 1SPOT W 5.5W 830 BK

#### Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

# Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
With light source	Yes
Replaceable light source	No

# Lifespan

Number of switching cycles	15000

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

# Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### **DOWNLOAD DATA**

	Documents and certificates Document name	
POF	User instruction / safety instructions	DECOR SPOT MOON
POF	Legal information	Safety insert G11219578
POF	Declarations of conformity	DECOR LUM
POF	Declarations of conformity UKCA	DECOR LUM

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854472190	Folding box 1	142 mm x 142 mm x 123 mm	490.00 g	2.48 dm <sup>3</sup>
4099854472206	Shipping box 4	290 mm x 150 mm x 260 mm	1960.00 g	11.31 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.