

PRODUCT DATASHEET Decor Spot Moon 2Spot 10.5W 830 Black

DECOR SPOT MOON | Ceiling mounted luminaires with adjustable spotlights



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

Product benefits

- High-quality look and feel
- Functional and minimalistic design
- Easy mounting

Product features

- Luminaire family features five versions with up to 4 spot heads
- Adjustable heads
- Housing material: metal



TECHNICAL DATA

Electrical data


Nominal wattage	10.50 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	80.000 mA	
Inrush current time T _{h50}	280 µs	
Max. number of luminaires per miniature circuit breaker B16	160	
Max. number of luminaires per miniature circuit breaker C10	100	
Max. number of luminaires per miniature circuit breaker C16	160	
Power factor λ	> 0.5	
Total harmonic distortion	62 %	
Protection class	I	
Operating mode	Mains voltage	

Photometrical data

Luminous flux	560 lm
Total luminous flux of contained light sources	1000 lm
Luminous efficacy	53 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	6 sdcm
Photobiological safety group acc. to EN62778	RG1
Beam angle	115°

Dimensions & Weight

Length	350.00 mm
Width	120.00 mm
Height	119.00 mm
Product weight	600.00 g



DECOR SPOT MOON 2SPOT 10.5W 830 BK

Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Terminal, 3-Pole (L, N, PE)	
Type of protection	IP20	
Protection class IK (shock resistance)	IK03	
Dimmable	No	
Mounting type	Surface	
With light source	Yes	
Replaceable light source	No	

Lifespan

Number of switching cycles	15000

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates Document name	
PDF	User instruction / safety instructions	DECOR SPOT MOON
PDF	Legal information	Safety insert G11219578
PDF	Declarations of conformity	DECOR LUM
PDF	Declarations of conformity UKCA	DECOR LUM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854472237	Folding box 1	136 mm x 172 mm x 323 mm	935.00 g	7.56 dm ³
4099854472244	Shipping box 4	336 mm x 284 mm x 369 mm	3740.00 g	35.21 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.