

# PRODUCT DATASHEET

## LED Spot Cup 3xG9 Brushed Nickel

LED Spot Cup | Ceiling mounted luminaires with adjustable G9 spotlights

---

### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, bedrooms, basements



---

### Product benefits

- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

---

### Product features

- Luminaire family features four versions with up to 4 spot heads
- Housing surface made of brushed nickel
- Diffuser made of alabaster glass
- Adjustable head




TECHNICAL DATA

Electrical data

|                  |               |
|------------------|---------------|
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50...60 Hz    |
| Protection class | I             |
| Operating mode   | Mains voltage |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 485.00 mm |
| Width          | 90.00 mm  |
| Height         | 170.00 mm |
| Product weight | 720.00 g  |



LED SPOT CUP 3XG9

Materials & Colors

|                                            |                |
|--------------------------------------------|----------------|
| Product color                              | Brushed nickel |
| Housing color                              | Brushed nickel |
| Body material                              | Steel          |
| Cover material                             | Glass          |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C         |

Application & Mounting

|                              |                         |
|------------------------------|-------------------------|
| Ambient temperature range    | -20...+40 °C            |
| Temperature range at storage | -20...+80 °C            |
| Type of connection           | Terminal, 2-Pole (L, N) |
| Type of protection           | IP20                    |
| Dimmable                     | No                      |
| Mounting type                | Surface                 |
| Mounting location            | Wall / Ceiling          |
| Adjustable                   | Yes                     |

|                          |    |
|--------------------------|----|
| With light source        | No |
| Replaceable light source | No |
| Holder designation       | G9 |

### Emergency lighting

|                                  |      |
|----------------------------------|------|
| Type of emergency operation test | None |
|----------------------------------|------|

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

### Additional product data

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Product remark        | Maximum bulb wattage: 5 W LED / Available from October 2025 |
| Number of illuminants | 3                                                           |

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name           |
|------------------------------------------------------------------------------------|----------------------------------------|-------------------------|
|  | User instruction / safety instructions | LED SPOT CUP G11238935  |
|  | Declarations of conformity             | LED SPOT CE declaration |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075852440 | Folding box<br>1             | 112 mm x 152 mm x 507 mm             | 1085.00 g    | 8.63 dm <sup>3</sup>  |
| 4058075852457 | Shipping box<br>4            | 325 mm x 245 mm x 530 mm             | 4910.00 g    | 42.20 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.