

PRODUCT DATASHEET

LED PFM CLAS A 9 W/6500 K E27 FR DIM

LED PERFORMANCE CLASSIC A DIMMABLE | LED lamps, classic bulb shape, with retrofit screw base



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- Very high dimmer compatibility, see also www.ledvance.com/dim
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Good quality of light
- Reliable operation thanks to brand quality

Product features

- Long lifetime up to 25,000 h
- Color rendering index $R_a: \geq 80$
- High color consistency: < 6 SDCM
- Luminous efficacy: up to 117 lm/W
- Mercury-free lamps



- Operating temperature from -20 °C to up to +40 °C, up to 95 % relative humidity

TECHNICAL DATA

Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	45 mA
Type of current	AC
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor λ	0.80

Photometrical data

Luminous flux	806 lm
Nominal useful luminous flux 90°	806 lm
Luminous efficacy	89 lm/W
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Standard deviation of color matching	≤6 sdc _m

Light technical data

Beam angle	240 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	108.00 mm
Diameter	61.50 mm
Product weight	80.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Number of switching cycles	100000
----------------------------	--------

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes
----------	-----

Country-specific categorizations

Order reference	LPCLADIM 9W/865
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	108.00 mm
Height	61.50 mm
Width	61.50 mm

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	LED PFM CLA 9W 6500K DIM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075215337	Folding box 1	64 mm x 64 mm x 131 mm	97.00 g	0.54 dm³
4058075215344	Shipping box 10	332 mm x 138 mm x 147 mm	1124.00 g	6.73 dm³
4058075378070	Shipping box 10	315 mm x 131 mm x 126 mm	1023.00 g	5.20 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.