

## PRODUCT DATASHEET

### LED VALUE CLAS B 4.9 W/6500 K B22d

LED VALUE CLASSIC B | LED lamps, classic mini-candle shape



#### Areas of application

- General illumination
- Domestic applications
- Chandeliers
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Simple direct replacement for conventional incandescent lamps
- Instant 100 % light, no warm-up time

#### Product features

- LED alternative to conventional lamps
- Not dimmable
- Good color rendering CRI  $\geq 80$  and color stability throughout the life of the lamp



TECHNICAL DATA

Electrical data

|                      |             |
|----------------------|-------------|
| Nominal wattage      | 4.9 W       |
| Construction wattage | 4.90 W      |
| Nominal voltage      | 220...240 V |
| Nominal current      | 42 mA       |
| Type of current      | AC          |
| Operating frequency  | 50/60 Hz    |
| Mains frequency      | 50/60 Hz    |

Photometrical data

|                           |          |
|---------------------------|----------|
| Luminous flux             | 470 lm   |
| Luminous efficacy         | 95 lm/W  |
| Light color (designation) | Daylight |
| Color temperature         | 6500 K   |
| Color rendering index Ra  | 80       |
| Light color               | 865      |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Overall length | 100.00 mm |
| Diameter       | 37.00 mm  |
| Product weight | 15.00 g   |

Temperatures & operating conditions

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Additional product data

|                             |      |
|-----------------------------|------|
| Base (standard designation) | B22d |
|-----------------------------|------|

Certificates & Standards

|                                              |      |
|----------------------------------------------|------|
| Type of protection                           | IP20 |
| Photobiological safety group acc. to EN62778 | RG0  |

Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | LVCLB404,9W/865 |
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015

|                                                     |           |
|-----------------------------------------------------|-----------|
| Light source cap-type (or other electric interface) | B22d      |
| Length                                              | 100.00 mm |
| Height                                              | 37.00 mm  |
| Width                                               | 37.00 mm  |

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075673564 | Folding box<br>1             | 51 mm x 51 mm x 123 mm               | 32.00 g      | 0.32 dm <sup>3</sup> |
| 4058075673571 | Shipping box<br>10           | 266 mm x 109 mm x 137 mm             | 443.00 g     | 3.97 dm <sup>3</sup> |
| 4099854256745 | Shipping box<br>10           | 266 mm x 109 mm x 137 mm             | 403.00 g     | 3.97 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.