

PRODUCT DATASHEET LED VALUE CLAS P 4.7 W/2700 K E27

LED VALUE CLASSIC P | LED lamps, classic mini-ball shape



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Color rendering index Ra; ≥ 80
- Not dimmable
- Mercury-free lamps



TECHNICAL DATA

Electrical data

| Nominal wattage | 4.7 W |
|--|----------|
| Construction wattage | 4.70 W |
| Nominal voltage | 220240 V |
| Claimed equiv. conventional lamp power | 40 W |
| Nominal current | 43 mA |
| Type of current | AC |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Power factor λ | > 0.50 |

Photometrical data

| Luminous flux | 470 lm |
|--------------------------------------|------------|
| Luminous efficacy | 100 lm/W |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | 80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcm |

Light technical data

| Beam angle | 150 ° |
|---------------|---------|
| Starting time | ≤ 0.5 s |

Dimensions & Weight

| Overall length | 82.00 mm |
|------------------|----------|
| Diameter | 45.00 mm |
| Maximum diameter | 45 mm |
| Product weight | 20.00 g |

Temperatures & operating conditions

| Ambient temperature range | -20+45 °C | |
|----------------------------|-----------|--|
| Lifespan | | |
| Lifespan L70/B50 at 25 °C | 15000 h | |
| Number of switching cycles | 100000 | |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------|--------|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |

Capabilities

Certificates & Standards

| Type of protection | IP20 |
|--|-----------------------|
| Standards | CB / EMC / SAA / ROHS |
| Photobiological safety group acc. to EN62778 | RG0 |

Country-specific categorizations

| Order reference LVCLF | P40 4,7W/82 |
|-----------------------|-------------|
|-----------------------|-------------|

LOGISTICAL DATA

Energy labelling regulation data acc EU 2019/2015

| Lighting technology used | LED |
|---|----------|
| Light source cap-type (or other electric interface) | E27 |
| Length | 82.00 mm |
| Height | 45.00 mm |
| Width | 45.00 mm |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854310287 | Folding box 1 | 45 mm x 45 mm x 84 mm | 29.00 g | 0.17 dm ³ |

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854310294 | Shipping box 10 | 233 mm x 98 mm x 96 mm | 351.00 g | 2.19 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.