

# PRODUCT DATASHEET DECOSTAR 51S 50 W 12 V 36° GU5.3

DECOSTAR® 51S Standard | Halogen dichroic reflector lamps with 51 mm diameter



#### Areas of application

- General illumination
- Entrance lighting
- Workplace lighting
- Kitchen lighting
- Mirror lighting
- Object lighting

#### Product benefits

- Brilliant accent light
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

#### **Product features**

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index Ra: 100
- Diameter: 51 mm
- Deco cover


## TECHNICAL DATA

## Electrical data

Nominal wattage	50 W	
Construction wattage	50.00 W	
Nominal voltage	12 V	

## Photometrical data

Luminous intensity	1450 cd	
Light color (designation)	Warm White	
Color temperature	3000 K	
Color rendering index Ra	100	
Light color	1030	
UV protection	Yes	



349643\_HAL\_DICRO\_AK

# Light technical data

Beam angle	36 °
Starting time	0 s

## Dimensions & Weight

Overall length	46.00 mm
Diameter	50.7 mm
Product weight	32.00 g

# Additional product data

Base (standard designation)	GU5.3
Mercury-free	Yes
Design / version	Reflector

# Capabilities

Dimmable	Yes

Burning position	Any	
Country-specific categorizations		
ILCOS	HRGS//UB-50-12-GU5.3-51/36	

44870 WFL

#### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	GU5.3
Length	46.00 mm
Height	50.7 mm
Width	50.7 mm

#### Safety advice

Order reference

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

#### **DOWNLOAD DATA**

Photometric and lighting design files	Document name	
Spectral power distribution	349643_HAL_DICRO_AK	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321279811	Folding box	46 mm x 46 mm x 58 mm	38.00 g	0.12 dm <sup>3</sup>
4008321279828	Shipping box 20	240 mm x 98 mm x 128 mm	820.00 g	3.01 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.