

PRODUCT DATASHEET

L 32W/865 G10Q

LUMILUX® T9 C | Circular fluorescent lamps 29 mm, with G10Q base



Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

Product benefits

- Excellent uniform illumination with no shadows

Product features

- Good color rendering index
- Single-ended round fluorescent lamp
- Dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	32 W
Construction wattage	32.00 W
Nominal voltage	84 V

Photometrical data

Luminous flux	2200 lm
Luminous efficacy	68 lm/W
Light color (designation)	LUMILUX Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80...89
Light color	865

Dimensions & Weight

Overall length	304.80 mm
Diameter	29.00 mm
Product weight	192.00 g

Lifespan

Lifespan B50	13000 h
--------------	---------

Additional product data

Base (standard designation)	G10q
Mercury content	3.0 mg

Country-specific categorizations

Order reference	L 32W/865 C G10
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G10q
Length	305.00 mm
Height	29.00 mm
Width	29.00 mm

EQUIPMENT / ACCESSORIES

– Suitable for operation on electronic and conventional control gears

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075718982	Sleeve 1	309 mm x 306 mm x 38 mm	322.00 g	3.59 dm ³
4058075718999	Shipping box 12	452 mm x 323 mm x 320 mm	4305.00 g	46.72 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.