

PRODUCT DATASHEET SPC.T FR 25 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



Areas of application

- Domestic baking ovens

Product features

– Ambient temperature: up to 300 $^{\circ}\text{C}$




TECHNICAL DATA

Electrical data

Nominal wattage	25 W
Construction wattage	25.00 W
Nominal voltage	230 V

Photometrical data

Luminous flux	140 lm
Luminous efficacy	5 lm/W
Lumen main.fact.at end of nom.life time	0.70
Color temperature	2700 K
Color rendering index Ra	> 99
Light color	927



349635_HAL_ohne_UVS

Light technical data

Starting time	0 s
---------------	-----

Dimensions & Weight



Overall length	57.00 mm
Length with base excl. base pins/connection	57.00 mm
Light center length (LCL)	45,0 mm

Diameter	26,0 mm
Product weight	7.6 g
Lifespan	
Lifespan L70/B50 at 25 °C	1000 h
Additional product data	
Base (standard designation)	E14
Mercury-free	Yes
Design / version	Frosted
Capabilities	
Dimmable	Yes
Certificates & Standards	
Energy efficiency class	G
Energy consumption	25.00 kWh/1000h
Country-specific categorizations	
ILCOS	IBT/F-25-230-E14-26
Order reference	SPC.T26/57 FR 2
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	No
Color-tuneable light source	No
Color-tuneable light source Envelope	No No
Envelope	No
Envelope High luminance light source	No No
Envelope High luminance light source Anti-glare shield	No No
Envelope High luminance light source Anti-glare shield Correlated colour temperature type	No No No SINGLE_VALUE
Envelope High luminance light source Anti-glare shield Correlated colour temperature type Standby power	No No No SINGLE_VALUE 0.00 W

26,0 mm

Height

Width	26,0 mm
Chromaticity coordinate x	0.487
Chromaticity coordinate y	0.416
Beam angle correspondence	SPHERE_360
EPREL ID	714464
Model number	AC35398,AC35398

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	Declarations of conformity	SPC.T26 57 OVEN	
POF	Declarations of conformity	OVEN 15W 25W E14	
	Photometric and lighting design files	Document name	
	Spectral power distribution	349635_HAL_ohne_UVS	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300323596	Folding box 1	27 mm x 27 mm x 61 mm	9.60 g	0.04 dm ³
4050300555195	Bundle 10	135 mm x 54 mm x 61 mm	96.00 g	0.44 dm ³
4050300555201	Shipping box 100	285 mm x 150 mm x 140 mm	1010.00 g	5.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.