

# PRODUCT DATASHEET Orbis Sparkle Remote-CCT 460mm 24W

ORBIS® Sparkle | LED ceiling luminaires with sparkling effect



### Areas of application

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

### Product benefits

- Very homogenous light
- Easy and quick installation

### **Product features**

- Ceiling luminaire with advanced LED technology
- Circular light emission



# TECHNICAL DATA

# Electrical data


Nominal wattage	28.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	180 mA
Max. number of luminaires per miniature circuit breaker B16	44
Max. number of luminaires per miniature circuit breaker C10	35
Max. number of luminaires per miniature circuit breaker C16	57
Power factor λ	> 0.5
Protection class	II
Operating mode	Integrated LED driver

# Photometrical data

Luminous flux	2000 lm
Total luminous flux of contained light sources	3120 lm
Luminous efficacy	93 lm/W
Color temperature	28006000 K
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °

# Dimensions & Weight

Diameter	500.00 mm
Height	91.00 mm
Product weight	800.00 g



PG ORBIS Sparkle 500mm 28W Remote MIPRC

### Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+70 °C
Type of connection	Terminal, 3-pin
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Mounting type	Surface
Application environment	Indoor
With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# **BATTERY**

Type of Battery	Alkaline
Battery size [GMS]	AAA
Nominal voltage of battery	1.5 V

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- Batteries required for remote control: 2xAAA (not included)

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Battery Warning: Keep out of reach for children. Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	ORBIS SPARKLE REMOTE CCT	
PDF	Legal information	Safety insert G11221927	
PDF	Declarations of conformity	ORBIS SPARKLE	
PDF	Declarations of conformity UKCA	Fixed LUM	

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854450228	Folding box 1	131 mm x 541 mm x 543 mm	1603.00 g	38.48 dm <sup>3</sup>
4099854450235	Shipping box 6	546 mm x 511 mm x 527 mm	9620.00 g	147.04 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.