

PRODUCT DATASHEET VALUE BAT 13.00 W 6500 K GEN3

LED VALUE BATTEN | LED batten luminaires



Areas of application

- Contour lighting
- Cove lighting
- Shelf lighting
- Backlighting
- Indoor applications

Product benefits

- Homogeneous light output
- Mercury-free technology

Product features

- $\,$ Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Lifetime up to 15,000 h
- Connection with 2-pin plug connection
- Beam angle: 120°
- Luminaire efficacy: up to 80 lm/W
- Power factor: 0.5
- CCC marked, CB test certificate



TECHNICAL DATA

Electrical data

Nominal wattage	13.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	110.000 mA
Power factor λ	0.50
Protection class	П
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	1200 lm
Luminous efficacy	80 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	≥70
Standard deviation of color matching	≤7 sdcm
Beam angle	120°

Dimensions & Weight

Length	1185.00 mm
Width	22.20 mm
Height	32.50 mm
Product weight	135.00 g



LDVAL BATTEN 1200 13W G3

Materials & Colors

Product color	White
Housing color	White
Body material Polycarbonate (PC) Polyvinyl chloride (PVC)	

Cover material	Polycarbonate (PC)	
Application & Mounting		
Ambient temperature range	-20+35 °C	
Temperature range at storage	-20+70 °C	
Type of protection	IP20	
Dimmable	No	
Mounting location	Ceiling / Wall	
Application environment	Indoor	
Replaceable light source	No	
Lifespan		
Number of switching cycles	15000	

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LED VALUE BATTEN 1200 13W 6500K G3 APM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075273559	Folding box 1	1,250 mm x 23 mm x 34 mm	215.00 g	0.96 dm ³
4058075273566	Shipping box 24	1,265 mm x 150 mm x 150 mm	5978.00 g	28.46 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.